



Coudes - Elbows

Coudes 90°/45° EN – R/S - S/S

PR = Petit rayon / GR = Grand rayon

RS = Roulé soudé / SS = Sans soudure

Désignations

12 x 1	PR R = 30
13,5 x 1,6	PR R = 20 GR R = 30
13,5 x 2,3	PR R = 20 GR R = 30
16 x 1	GR R = 40
17,2 x 1,6	PR R = 25 GR R = 30
17,2 x 2,3	PR R = 25 GR R = 30
18 x 1,5	PR R = 37 GR R = 45
20 x 1	PR R = 37 GR R = 55
20 x 1,5	PR R = 37 GR R = 55
21,3 x 1,6 P	PR R = 38 PR R = 45
21,3 x 1,6	PR R = 38 GR R = 45
21,3 x 2 P	PR R = 27
21,3 x 2	PR R = 38 GR R = 45
21,3 x 2,6 P	PR R = 27
21,3 x 2,6	PR R = 38 GR R = 45
22 x 1	PR R = 40 GR R = 65
23 x 1,5	PR R = 30
23 x 1,5	GR R = 60
25 x 1	GR R = 65
25 x 1,5	PR R = 37
25 x 2	PR R = 37
26,9 x 1,6	PR R = 28

Désignations

	GR R = 57
26,9 x 2	PR R = 28 GR R = 57
26,9 x 2,6	PR R = 28 GR R = 57
28 x 1,5	PR R = 37 GR R = 80
30 x 2	PR R = 38
33 x 1,5	PR R = 45 GR R = 90
33,7 x 1,6	PR R = 38 GR R = 72
33,7 x 2	PR R = 38 GR R = 72
33,7 x 3,2	PR R = 38 GR R = 72
38 x 1,5	PR R = 52 GR R = 105
38 x 2	PR R = 52
38 x 2,6	PR R = 45
40 x 1,5	PR R = 60
42,4 x 1,6	PR R = 47 GR R = 92
42,4 x 2	PR R = 47 GR R = 92
42,4 x 2,6	PR R = 47
42,4 x 3,2	PR R = 47 GR R = 92
43 x 1,5	PR R = 60 GR R = 120
44 x 2	PR R = 60 GR R = 120
33,7 x 2	PR R = 38 GR R = 72

Désignations

44,5 x 2	PR R = 51
48,3 x 1,6	PR R = 57
48,3 x 1,6 sm	GR R = 95
48,3 x 1,6	GR R = 109
48,3 x 2	PR R = 57
48,3 x 2 sm	GR R = 95 S
48,3 x 2	GR R = 109
48,3 x 3,2	PR R = 57 GR R = 109
51 x 1,5	PR R = 75
51 x 2,6	PR R = 75
53 x 1,5	PR R = 75 GR R = 150
54 x 2	PR R = 75 GR R = 150
60,3 x 1,6	PR R = 76 GR R = 137
60,3 x 2	PR R = 76
60,3 x 2 sm	GR R = 114
60,3 x 2	GR R = 137
60,3 x 2,6	PR R = 76
60,3 x 3,6	PR R = 76 GR R = 137
63,5 x 1,6	PR R = 90 GR R = 180
63,5 x 2,6	PR R = 90
64 x 2	PR R = 90 GR R = 180
69 x 2	PR R = 95 GR R = 130
70 x 2	PR R = 95 GR R = 130
73 x 1,5	PR R = 95
74 x 2	PR R = 95

Désignations

	GR R = 140
76,1 x 1,6	PR R = 95
76,1 x 2	PR R = 95 GR R = 175
76,1 x 2,9	GR R = 175
76,1 x 3	PR R = 95
76,1 x 3,6	PR R = 95
76,1 x 3,6 P	GR R = 150
76,1 x 3,6	GR R = 175
84 x 2	PR R = 120 GR R = 160
88,9 x 2	PR R = 114 GR R = 207
88,9 x 3	PR R = 114 GR R = 207
88,9 x 4	PR R = 114 GR R = 207
101,6 x 2	PR R = 133
101,6 x 4	PR R = 133
104 x 2	PR R = 150 GR R = 200
114,3 x 2	PR R = 152 GR R = 270
114,3 x 3	PR R = 152 GR R = 270
114,3 x 4,5	PR R = 152 GR R = 270
129 x 2	PR R = 188
139,7 x 2	PR R = 190
154 x 2	PR R = 225
168,3 x 2	PR R = 228
204 x 2	PR R = 300
219,1 x 2	PR R = 305

8

Coudes
Elbows

Coudes 90°/45°

Long rayon / Court rayon

Roulé Soudé (= R/S) / Sans Soudure (= S/S)

Désignations	
1/4" 10S LR	13,7 x 1,65 R = 20
40S LR	x 2,24
80S LR	x 3,02
3/8" 10S LR	17,1 x 1,65 R = 25
40S LR	x 2,31
80S LR	x 3,20
1/2" 5S LR	21,3 x 1,65 R = 38
10S LR	x 2,11
40S LR	x 2,77
80S LR	x 3,73
160S LR	x 4,75
DEF LR	x 7,47
3/4" 5S LR	26,7 x 1,65 R = 28
10S LR	x 2,11
40S LR	x 2,88
80S LR	x 3,91
160S LR	x 5,54
DEF LR	x 7,82
1" 5S LR	33,4 x 1,65 R = 38
10S LR	x 2,77
40S LR	x 3,38
80S LR	x 4,55
160S LR	x 6,35
DEF LR	x 9,10
1 1/4" 5S LR	42,2 x 1,65 R = 47
10S LR	x 2,77
40S LR	x 3,56
80S LR	x 4,85
160S LR	x 6,35

Désignations	
DEF LR	x 9,70
10S SR	42,2 x 2,77 R = 32
1 1/2" 5S LR	48,3 x 1,65 R = 57
10S LR	x 2,77
40S LR	x 3,68
80 LR	x 5,08
160S LR	x 7,14
DEF LR	10,1 x 10,20
5S SR	48,3 x 1,65 R = 38
10S SR	48,3 x 2,77 R = 38
40S SR	x 3,68
2" 5S LR	60,3 x 1,65 R = 76
10S LR	x 2,77
40S LR	x 3,91
80S LR	x 5,54
160S LR	x 8,70
DEF LR	x 11,10
5S SR	60,3 x 1,65 R = 51
10S SR	x 2,77
40S SR	x 3,91
2 1/2" 5S LR	73,0 x 2,11 R = 95
10S LR	x 3,05
40S LR	x 5,16
80S LR	x 7,01
160S LR	x 9,52
DEF LR	x 14,00
5S SR	73,0 x 2,11 R = 63
10S SR	x 3,05
40S SR	x 5,16

Désignations	
3" 5S LR	88,9 x 2,11 R = 114
10S LR	x 3,05
40S LR	x 5,49
80S LR	x 7,62
160S LR	x 11,10
DEF LR	x 15,20
5S SR	88,9 x 2,11 R = 76
10S SR	x 3,05
40S SR	x 5,49
3 1/2" 5S LR	101,6 x 2,11 R = 133
10S LR	x 3,05
40S LR	x 5,74
80S LR	x 8,08
4" 5S LR	114,3 x 2,11 R = 152
10S LR	x 3,05
40S LR	x 6,02
80S LR	x 8,56
160S LR	x 13,50
5S SR	114,3 x 2,11 R = 101
10S SR	x 3,05
40S SR	x 6,02
5" 5S LR	141,3 x 2,77 R = 190
10S LR	x 3,40
40S LR	x 6,55
80S LR	x 9,53
5S SR	141,3 x 2,77 R = 127
10S SR	x 3,40
40S SR	x 6,55
6" 10S LR	168,3 x 3,40 R = 228

Nous consulter
pour toutes autres
cotes.
Call us for special
sections or
special qualities